

| MAXXIMIZER PACKAGE CHILLER ASSEMBLIES |                                  |           |                         |                  |                 |         |                                         |
|---------------------------------------|----------------------------------|-----------|-------------------------|------------------|-----------------|---------|-----------------------------------------|
| Horsepower                            | Number of Refrigeration Circuits | Voltage   | Glycol Connections (in) | Flow Range (gpm) | Head Range (ft) | Btu/hr1 | Approximate Shipping Weight Crated (lb) |
| R-507 Refrigerant                     |                                  |           |                         |                  |                 |         |                                         |
| 40                                    | 4                                | 230/60/3  | 3                       | 100-300          | 35-65           | 340,800 | 4,800                                   |
| 40                                    | 4                                | 460/60/3  | 3                       | 100-300          | 35-65           | 340,800 | 4,800                                   |
| R-448A Refrigerant                    |                                  |           |                         |                  |                 |         |                                         |
| 40                                    | 4                                | 230/60/3  | 3                       | 100-300          | 35-65           | 288,000 | 4,800                                   |
| 40                                    | 4                                | 460/60/3  | 3                       | 100-300          | 35-65           | 288,000 | 4,800                                   |
| 40                                    | 4                                | 575/60/32 | 3                       | 100-300          | 35-65           | 288,000 | 4,800                                   |

*All MAXXimizer chillers are equipped with two 5-horsepower water circulation pumps.  
Based on compressor manufacturer's data at 20°F SST and 100°F CT. Actual Btu/hr output and energy usage may vary depending on field conditions.  
230 V/ 60 Hz fan motor circuit.*